

High-end Fusion Splicer
S185HS / S185PM
for High strength splicing for PMF & High strength splicing



S185HS



S185PM

Fusion Splicers for PMF and High strength splicing

Low splice loss

Compact size

High capacity built-in battery (Optional)

LCD touch panel provides easy operation


Short fiber cleave length allows to use ultra mini sleeve

Remote control by Wi-Fi communication

The FITEL S185HS / S185PM High-end Fusion Splicers are designed for splicing specialty fibers for factory, manufacturing and R&D applications. The compact but powerful design has been optimized for use in the optical component and optical sensor fields. By targeting the necessary functions in these applications, exceptional performance and a compact design are achieved with these High-end Fusion Splicers


■ Features

Low splice loss




Precise alignment with resolution of 0.03 μm for fiber axis.

High ext. ratio



Accurate 360 degree fiber rotation with a resolution of 0.1 degree

Compact size




Footprint is 46% smaller than previous model.

Built-in battery




Battery operation and a compact design make transportation easy.

Touch panel



Easy and intuitive touch panel operation and GUI.

Short cleave length



Short cleave length allows to reinforce the exposed glass with ultra mini sleeve.

Wi-Fi communication



Remote control is available by Wi-Fi.

Auto-flip display



Automatically adjusts image when LCD display is flipped.

Specification

Description	S185HS	S185PM
Applicable fibers*1	SM, MM, DS, NZDS, High-Index, EDF	SM, MM, DS, NZDS, High-Index, EDF, PMF
Cladding diameter	80 to 150 μm	
Coating diameter	160 to 2000 μm (In Fiber holder) 160 to 900 μm (Coating clamp splice)	160 to 1300 μm (In Fiber holder) 160 to 900 μm (Coating clamp splice)
Fiber cleave length	3 to 4 mm (Coating clamp splice) 8 to 11 mm (Cladding clamp splice)	
Typical splice loss*2	SM (ITU-T G652): 0.014 dB	
Typical extinction ratio*2	-	PANDA: 40 dB*3 (Angle offset: 0.6 degree)
Return loss	>60 dB	
Typical splice time*4	15 s (SM by cladding clamp splice)	15 s (SM by cladding clamp splice) 40 s (PANDA by cladding clamp splice)
Tension strength	1.96 N (+0% to +20%)	
Applicable protection sleeve length	10 to 60 mm	
Typical heat time	35 s (S922:40 mm sleeve)	
Splice programs	Max.200	
Heater programs	Max.100	
Splice data storage	Max. 1000 including 4 images before and after splice	
Fiber image magnification on LCD	104 X, 278 X or 556 X	
Dimension	210 W x 180 D x 150 H mm	
Weight (without Battery)	4.5 kg	4.75 kg
Monitor	4.3" wide color LCD with touch panel	
Data output	USB ver. 2.0 type A: 1 port USB ver. 2.0 mini B: 1 port	
Battery capacity (Optional)*5	Typical 60 splice / heat cycles	
Operating temperature	0 to 40°C	
Storage temperature	-40 to 60°C	
Humidity	0 to 90% (Non-condensing)	
Power source	AC input 100 to 240 V (50/60 Hz)	

*1 Fibers should be applied to ITU-T standard. In case of other fibers, depending on the type of fiber, the optimization of splice program may be needed or the splice result may not be satisfied.

*2 These are references. Depending on the environment and condition, the number vary.

*3 Extinction ratio 40 dB is measured in the condition that the initial extinction ratio is more than 50 dB and there is the splice with 0.6 degree of rotation offset.

*4 This value is references. Depending on the type of fiber and condition of fiber on splicer, the number can vary.

*5 This value can produce using fully charged brand new battery at room temperature 20 degree C. Depending on the condition of the battery and operation environment, the number can vary.

Standard package

Item	P/N	Quantity							
		S185HS				S185PM			
		-00	-01	-10	-11	-00	-01	-10	-11
S185HS Main body	S185HS-X-A-0001	1	1	1	1	-	-	-	-
S185PM Main body	S185PM-X-A-0001	-	-	-	-	1	1	1	1
Hard Carrying Case	HCC-12	-	1	-	1	-	1	-	1
Built-in Battery Pack	S947B	-	-	1	1	-	-	1	1
AC Adapter	S981A	1	1	1	1	1	1	1	1
AC Cable Cord	-	1	1	1	1	1	1	1	1
Z Stage Lock	ZL-01	1 pair	1 pair	1 pair	1 pair	1 pair	1 pair	1 pair	1 pair
Spare Electrode	ELR-03	1 pair	1 pair	1 pair	1 pair	1 pair	1 pair	1 pair	1 pair
Electrode Sharpener	D5111	1	1	1	1	1	1	1	1
Cleaning Brush	VGC-01	1	1	1	1	1	1	1	1
User Manual	-	1	1	1	1	1	1	1	1



Standard Package (S185PM)



Hard Carrying Case

Ordering number form

S185 A - B C

Mark	Category	Code	Remark
A	Splicer model	HS	S185HS
		PM	S185PM
B	Battery	0	None
		1	Included
C	Hard carrying case	0	None
		1	Included

Optional components

Item	P/N	Quantity
160μm Coating Fiber Holder	S713S-160	1 pair
250μm Coating Fiber Holder	S713S-250	1 pair
300μm Coating Fiber Holder	S713S-300	1 pair
400μm Coating Fiber Holder	S713S-400	1 pair
550μm Coating Fiber Holder	S713S-550	1 pair
650μm Coating Fiber Holder	S713S-650	1 pair
900μm Coating Fiber Holder	S713S-900	1 pair
1300μm Coating Fiber Holder	S713S-1300	1 pair
550μm Coating BW Fiber Holder	S713B-550	1 pair
Customized Fiber Holder*6	S713S-XXX	1 pair
Hard Carrying Case	HCC-12	1
Built-in Battery Pack*7	S947B	1
USB Cable	USB-01	1
Wi-Fi Dongle	WFD-01	1



Fiber Holder

*6 Available Suitable size Fiber holder depending on the coating diameter of splicing fiber.


*7 Built-in Battery Pack should be installed by the authorized distributor or the repair center in Furukawa Electric group.

Related tools

Item	Part Number	Specification
Stripper	S218R-Plus	Cladding diameter 125μm only
	3SAE Thermal Stripper	Cladding diameter 80 to 1000μm
Cleave	S326S80	Cladding diameter 80μm only
	S326A	Cladding diameter 125μm only
	NorthLab ProCleave SD	Cladding diameter 80 to 250μm
Cleaner	3SAE Ultrasonic Cleaner	-
Protection sleeve	S921/S922	Coating diameter 900μm or less
	S928A-20/25/35	Coating diameter 400μm or less
Fiber end face interferometer & microscope	NorthLab Proview	Cladding diameter 125 to 720μm



S218R-Plus



3SAE Thermal Stripper



S326S80




S326A




NorthLab ProCleave



3SAE Ultrasonic Cleaner



Protection sleeve



NorthLab Proview

Contact Us :

FURUKAWA ELECTRIC CO., LTD.

Head Office:

Tokiwabashi Tower,
2-6-4, Otemachi, Chiyodaku,
Tokyo 100-8322, Japan
Tel: + 81-3-6281-8500
www.furukawa.co.jp
fec_abr_opt_splicer@furukawaelectric.com

Europe:

Furukawa Electric Europe Ltd.
Furukawa House,
2 Farriers Yard,
London, W6 8AH, UK
Tel: + 44-(0)-20-7313-5300
Fax: + 44-(0)-20-7313-5310
www.furukawa.co.uk
splicers@furukawa.co.uk

North & South America:

OFS Fitel, LLC
2000 Northeast Expressway
Norcross, Georgia 30071, U.S.A
Toll free: + 1-866-452-9516
Tel: + 1-678-783-1090
Fax: + 1-678-783-1093
www.ofsoptics.com
splicers@ofsoptics.com

China:

Furukawa Shanghai, Ltd.
Beijing Branch
Room 314, Beijing Fortune Building,
No.5, North Dongsanhuan Road,
Beijing 100004 P.R. China
Tel: + 86-10-8591-0608
Fax: + 86-10-8591-0609
www.furukawa-sh.cn

South East Asia:

Furukawa Electric Singapore Pte. Ltd.
60 Albert Street, #13-10 OG
Albert Complex, Singapore
189969
Tel: + 65-6224-4686
Fax: + 65-6336-2635
comms@furukawa.com.sg

* Please understand that contents of this catalog may change without notice.

Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in Japan.

In addition, the Export Administration Regulations (EAR) of the United States may be applicable.

In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost.

Please contact the Ministry of Economy, Trade and Industry of Japan or the Department of Commerce of the United States for details about procedures.